



# AVT WEAR STUDS

**NEW**

**AVT**  
ANTI-WEAR TECHNOLOGY  
Wear Studs

- Reduces wear on surfaces exposed to abrasion by forming a barrier between the machinery and the material being moved.
- Consists of applying high-chromium and high-carbon abrasion resistant studs to machinery in close formation.
- Easy to handle, fast application welding gun saves time and labour costs.



## FEATURES & BENEFITS

- High abrasion resistance
- Quick & easy application on site
- Permanent protection
- Save on time, power and labour
- Minimise costs and machine down time
- Extend machinery wear life

## APPLICATIONS

- Deep Mining Industry
- Open Pit Mines
- Quarries
- Tunneling
- Steelworks
- Ore Preparing



## Effectiveness of AVT wear studs in different ground conditions

Ground Condition	Rock-Box-Effect	Impact	Effectiveness
Sand	★★★	Low	★★★
Sand & gravel	★★★	Low	★★★
Gravel & earth, loose	★★★	Low	★★★
Earth, loose	★★★	Low	★★★
Earth & clay	★★★	Low	★★★
Clay & shale loose	★★★	Low	★★★
Shale, tight, blasted	★★	High	★★
Shale & coal, tight, blasted	★★	Moderate	★★
Shale & coal, loose	★★★	Low	★★★
Lignite, sub bituminous coal	★★★	Moderate	★★★
Bituminous coal, blasted	★	Moderate	★★
Anthracite, blasted	★	Moderate	★★
Limestone, blasted	★	High	★
Sandstone & earth, loose	★★★	Moderate	★★
Sandstone, tight, blasted	★	High	★
Phosphate loose or blasted	★★★	Low	★★★
Uranium ore, loose	★★★	Moderate	★★★
Copper ore, loose	★★★	Moderate	★★★
Mineral ores, loose	★★★	Moderate	★★★
Tight areas, blasted	★	High	★
High quartzite, loose or blasted	★	High	★

★ = Poor    ★★ = Fair    ★★★ = Good

### Available in 3 specifications:

Note that all studs include ceramic shield. Other sizes available on request.

#### Standard

- 16mm with 13mm neck; and
- 20mm with 17mm neck
- Length is 15mm
- Fits standard chucks
- Made for Australian conditions
- Hardness 58-60HRC

#### Premium

- 16mm with 10mm neck
- Length is 15mm
- Tapered top fits perfectly into the chuck
- Fast loading
- Fits standard chucks
- Hardness 58-60HRC

#### High Performance

- 16mm with 12mm neck
- Length is 15mm
- Tungsten Carbide insert for higher wear resistance
- Use across 10-20% of total surface area for additional durability
- Insert Hardness is HV1,200

Product	Part Number
Standard M16	EAW13-16-015S
Standard M20	EAW17-20-015S
Premium M16	EAW10-16-015PR
High Performance	EAW12-16-015H8



Distributed by:  
**ANTEC ENGINEERING PTY LTD**  
 9 Chicago Avenue, Blacktown, NSW, 2148, Australia  
 Ph : +61 (02) 9622-9622 • Fax: +61 (02) 9622-9199  
[www.antecon.com.au](http://www.antecon.com.au)